



4802 - Beige White
1% Openness

| | |
|---------------------------|--|
| Fabric Width | 72" - 98" - 118" |
| Fabric Composition | 30% Polyester, 70% PVC |
| Mesh/in | N/A |
| Weight | 20.350 oz./yd. ² - 690 g/m ² |
| Fabric Thickness | ± 1.02 mm |
| Openness Factor | 1% |
| UV Blockage | Approximately 99% |
| Color Fastness | Class 4.5 (AATCC 16-2003) |
| Fire Resistance | NFPA701 (USA) |
| Environment | OEKO-TEX 100 |

| Transmittance | Reflection | Absorption |
|---------------|------------|------------|
| 6 | 63 | 31 |

Certifications



The Greenguard Environmental Institute is an industry-independent organization that aims to protect human health and improve quality of life by enhancing indoor air quality and reducing people's exposure to chemicals and other pollutants.



Oeko-Tex Standard 100 or Oeko-Tex Standard 100 is an independent testing and certification system for textile products from all stages of production along the textile value chain.



Fire Reaction Certificate
NFPA - 701-1999 (USA)

In the case of draperies, curtain, and similar hanging textiles, the standard that applies is NFPA 701: Standard methods of fire tests for flame propagation of textiles and films this test measures the flammability of a fabric when it is exposed to specific sources of ignition.

Fabric color pictured above can vary from printers.
Please see an actual sample piece for true color.