



<b>General:</b>	Assembled by A&I Manufacturing, Inc. <b>Environmentally safe.</b>
<b>Fabric:</b>	Translucent or Room Darkening spun lace, non woven fabric. 100% Polyester.
<b>Head Rail:</b>	3/4" High x 1 5/8" deep extruded aluminum with PVC end caps. Depth with installation bracket is 2".
<b>Slat Insert:</b>	Cold rolled spring tempered virgin aluminum slat. To have normal width of 1" and be 0.006" thickness after paint. Valance to be finished with a polyester baked enamel. Color coordinated to match the fabric.
<b>Bottom Rail:</b>	1/2" High x 1 5/8" deep extruded aluminum with PVC end caps.
<b>Cord Lock:</b>	Cord lock shall be secured to the head rail channel. Lock body shall be constructed of clear polycarbonate,. Floating gear and pins locks shall e made of brass. Cord lock to be of crash-proof design.
<b>Cord Cleat:</b>	Cleat is made of clear 100% PVC.
<b>Lift Cord:</b>	Shall be braided polyester and of sufficient length to control the raising and lowering of the shade. Outside diameter is 0.9mm.
<b>Tassel:</b>	100% PVC. Shall comply with all safety requirements.
<b>Stop Ball:</b>	100% PVC. Shall comply with all safety requirements.
<b>Installation Brackets:</b>	Constructed of cold rolled steel. Zinc plated. Intermediate brackets spaced no wider than 36" apart.
<b>Sizes:</b>	Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal shades will have 1/2" deducted at the factory from width. <i>See Product Limits.</i>

### Product Limits

Controls (Manual)	Min. Width	Max. Width	Min. Drop	Max. Drop
Standard	7"	144"	5"	*144"

Maximum Sq. Footage \*100 Sq. Ft. Under Warranty

\* Exceptions Available Upon Request

	<b>WARNING</b>		<b>ADVERTENCIA</b>
	Cords on window covering products present a potential strangulation hazard.		Las cuerdas y cadenas y persianas presentan un peligro de estrangulación.
	For child safety, consider cordless alternatives or products with inaccessible cords.		Para la seguridad de los niños, considere alternativas sin cuerdas o productos con cuerdas y cadenas inaccesibles.
<small>SAFLAB-3 04/2013</small>	<small>ANSI/WCMA 5.1.4</small>	<small>SAFLAB-3 04/2013</small>	<small>ANSI/WCMA 5.1.4</small>

